

OPERATION MANUAL OF 220 V COMBINED OIL PUMP

1、 Performance features: fast self-priming, fast lift, small size, easy to carry. Various oil guns and movable joints can be selected according to customer's requirements, making it more convenient to use.

2、 Application: oil consumption equipment such as mining machinery, generator set, fishing boat, yacht and small refueling point, etc.

3、 Oil pump features: cast iron pump body, anti-corrosion, inside and outside filter, easy to clean, aluminum alloy motor.

4、 Technical parameter:

Voltage: 220V power: 1100W flow: 120L/min

Suction head: 5-8m pressure: 0.3MPa medium: diesel、Kerosene

5、 Precautions for use

(1) Check whether the power supply is consistent.

(2) When the refueling pump is used for the first time, a little pumping fluid should be added into the pump head to enhance the suction. The direction of oil inlet and outlet is shown by the arrow.

(3) Before use, please ensure that there is no air leakage in the oil inlet pipe to ensure the suction head.

(4) It is suitable for diesel, kerosene, not for low ignition point such as gasoline, LPG, alcohol, etc.

6、 Common troubleshooting

(1)If the oil inlet pipe leaks, check the oil pipe and lock the pipe joint.

(2)If the suction head and lift exceed the standard, the oil output will be reduced, so the suction head and lift should be adjusted.

(3)If the oil inlet is blocked by impurities, the foreign matters shall be removed in time.

(4)The blade is worn and the oil output is reduced, so the blade should be replaced.



Add.: No 7, No 3 Modern Industrial Park, Fengcheng city,
Liaoning Province.

Tel: 0415-3512268 3512288

Fax: 0415-3512278

After-Sales service telephone: 0415-3512298

Postcode: 118100

Website: www.fcjunmin.com

E-mail : fcjunmin@126.com